

<b>TEKNİK ÖZELLİKLER / TECHNICAL PROPERTIES</b>	<b>ÜRÜN/ PRODUCT BATYLINE ISO FR</b>	<b>STANDARTLAR / STANDARDS</b>
Ağırlık / Weight	500 g/m <sup>2</sup>	EN ISO 2286-2
En / Width	180 cm	
Delik oranı / Porosity	%22	
<b>FİZİKSEL ÖZELLİKLER / PHYSICAL PROPERTIES</b>		
Kopma Mukavemeti / Tensile Strength	240/240 DaN / 5cm	EN ISO 1421
Yırtılma Mukavemeti / Tear Strength	40/40 DaN	DIN 53.363
Sürtünme mukavemeti / Abrasion resistance	120.000 tur / 120.000 cycles	EN ISO 12947-2
Işık mukavemeti / Extreme light stability	Δ E lab <3 , UVA 340 /2000h	NF T30 -036(QUV TEST)
Mold resistance / Küflenmeye karşı direnci	Degree 0, Excellent / Harika	ISO 846 Method A
Isıya Dayanım / Extreme working temperatures	-30 C / +70 C	
<b>FLAME RETARDANCY / ALEV YÜRÜMEZLİK</b>		
Rating / Değerlendirme	<ul style="list-style-type: none"><li>• <b>M2</b> / NFP 92-503 / NFP 92-503</li><li>• <b>B1</b> /DIN 4102-1</li></ul>	
EUROCLASS	B-S2,d0	<ul style="list-style-type: none"><li>• EN 13501-1</li></ul>
<b>MANAGEMENT SYSTEMS / İŞLETİM SİSTEMLERİ</b>		
Quality / Kalite		ISO 9001
Environment / Çevre		ISO 14001
<b>CERTIFICATIONS / SERTİFİKALAR</b>		

